








KEY FEATURES AND HIGHLIGHTS

- ⚙️ **Wireless Voice Quality with Advanced QoS**
 - 30 Simultaneous voice calls per IronPoint Mobility Access Point
 - 5 times more than traditional wireless networks
 - Zero packet-loss and zero delay handoffs for true seamless roaming
 - Automatic detection and prioritization of SIP, H.323, Spectralink and Vocera voice protocols
- ⚙️ **Unmatched performance in high density deployments**
 - Supports 100 active clients per IronPoint Mobility Access Point
 - A 10-fold increase over other access points
 - Automatic RF coordination eliminates co-channel interference in microcell deployments
- ⚙️ **Data Privacy with multi-layer security policies**
 - Wi-Fi Alliance Certified interoperability for WPA security
 - Automatic rogue access point detection and prevention without degradation of client traffic
 - Multiple ESSIDs with individual security policies to ensure separation of different user groups
- ⚙️ **Centralized management for ease of deployment**
 - Automatic discovery and configuration of IronPoint Mobility Access Points over any network topology
 - Easy management through CLI, GUI, and IronView Network Manager

SPECIFICATIONS

			
MOBILITY CONTROLLER FEATURES	MC500	MC1000	MC3000
Application	Remote/Small Office	Small/Medium Enterprise	Large Enterprise/Campus
WiFi Certification	Yes	Yes	Yes
Maximum Mobility Access Points	5	30	150
Uplink Ethernet Interfaces	Dual Fast Ethernet 10/100 Mbps	Dual GbE 10/100/1000 Mbps	Dual GbE 10/100/1000 Mbps
Console Interface	Yes	Yes	Yes
External LCD	No	Yes	Yes
Power Consumption	27W	200W	300W
Dimensions	1.4"x7.6"x5.0"	1.75"x17.0"x13.1"	1.75"x17.0"x16.25"
Mounting	Mini-desktop	1U rack mount	1U rack mount

		
ACCESS POINT FEATURES	AP208	AP201
802.11a/b/g Radios	2	1
WiFi Certification	Yes	Yes
Power over Ethernet	802.3af	802.3af
External DC Power	3.3V	3.3V
Antenna Connectors	RP-SMA female	RP-SMA female
External Antenna Options	Yes	Yes
Ethernet Interface	Fast Ethernet 10/100 Mbps	Fast Ethernet 10/100 Mbps
Console Interface	Yes	Yes
Dimensions	1.5"x6.25"x8.25"	1.5"x6.25"x8.25"
Mounting	Wall/ceiling mount UL2545 Plenum-rating	Wall/ceiling mount UL2545 Plenum-rating
Physical Security	Kensington MicroSaver Lock compatible	Kensington MicroSaver Lock compatible